HITACHI

Combination Multi Head options

IVX system

Multi Head options

Model: Outdoor Unit	RAS-4HVNC1	RAS-5HVNC1	RAS-6HVNC1
Capacity (kW)			
Nominal Cooling Capacity	10.0 (4.5 - 11.2)	12.5 (5.7 - 14.0)	13.0 (6.0 - 16.0)
Nominal Heating Capacity	11.2 (5.0 - 14.0)	14.0 (5.0 - 18.0)	16.0 (5.0 - 20.0)
Multi Head Connection			
No. of Indoor Units Connectible (min/max)	2 / 4	2 / 4	2 / 4
Indoor Unit Capacity Connectable of Max kW	10.0 - 12.7	12.4 - 15.1	14.7 - 18.3
Ratio Largest / Smallest Indoor Unit	2 : 1	2 : 1	2 : 1

Combination Multi Head

Outdoor Unit (kW)		4.5 - 11.2	5.7 - 14.0	6.0 - 16.0
	RAS	✓	✓	✓

Indoor Unit (kW)		2.2	2.8	4.0	5.6	7.1	8.0	11.2	14.0
	4 Way Cassette (RCI)	–	✓	✓	✓	✓	✓	✓	✓
	Mini 4 Way Cassete (RCIM)	–	✓	✓	✓	–	–	–	–
	2 Way Cassette (RCID)	–	✓	✓	✓	✓	✓	✓	✓
	Ducted (RPI)	✓	✓	✓	✓	✓	✓	✓	✓
	Under Ceiling (RPC)	–	–	✓	✓	✓	✓	✓	✓
	Wall (RPK)	–	✓	✓	✓	✓	✓	✓	–

✓ COMBINATION – N/A